

Model	<i>FS-300</i>
Rated Power	350W
LED Total Power	330W
Input Voltage/Current	AC100-240V 50/60Hz
CRI	96
TLCI	98
CCT	5600K
Dimming	0-100%
Control	On-board controller, 2.4G, Bluetooth
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light fixture(Without protective cap but with yoke): 342.5×232×123mm/13.48×9.13×4.84" Light fixture(Without protective cap and yoke): 311.5×156×123mm/12.26×6.14×4.84"
Product Weight	Light fixture: 2.95kg/6.49lb Power cable 4.5M: 0.4kg/0.88lb Reflector: 0.2kg/0.44lb
Configuration	FS-300×1 Power cable 4.5M×1 Reflector×1 User manual×1
Certifications	CE, PSE, ETL, cETL, NCC, KUCAS, ROHS

Illumination(lux /fc)

Distance	1M	2M	3M
Light only	12550 lux / 1166 fc	3074 lux / 286 fc	1447 lux / 134 fc
With reflector	41040 lux / 3813 fc	8852 lux / 822 fc	3780 lux / 351 fc
With Fresnel Lens spot	50380 lux / 4680 fc	10480 lux / 974 fc	4387 lux / 408 fc
With Fresnel Lens flood	22610 lux / 2100 fc	5658 lux / 526 fc	2515 lux / 234 fc