

Model	Forza 300 II
Rated Power	350W
Input Voltage/Current	DC(Battery)14.4V-14.8V/12A, AC100-240V 50/60Hz
Beam Angle	120°
CCT	5600K(G/M±80)
CRI	96
TLCI	97
TM-30 Rf	Average 94
TM-30 Rg	Average 102
Dimming	0-100%, by 1% increment
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
Product Size	Light Fixture (without COB protective cap): 330 × 228 × 123mm / 12.99 × 8.98 × 4.84" Control Unit: 156 × 139 × 232mm / 6.14 × 5.47 × 9.13"
Product Weight	Light Fixture: 2.88kg / 6.35lb Control Unit: 2.45kg / 5.4lb AC Power Cable 6M: 0.55kg / 1.21lb DC Connection Cable 3M: 0.47kg / 1.04lb Quick Release Clamp: 0.6kg / 1.32lb Reflector: 0.2kg / 0.44lb
Master Carton Size	550 × 380 × 610mm / 21.65 × 14.96 × 24.02"
Packing Quantity	2
Certification	RoHS, NCC, FCC-ID, CE, PSE, KCC, ETL, cETL

Illumination (lux / fc)

Distance	1M	3M	5M
Light Only	14270 lux	1713 lux	696 lux
	1326 fc	159 fc	65 fc
With Reflector	69400 lux	6321 lux	2340 lux
	6447 fc	587 fc	217 fc
With FL-20G spot 10°	197000 lux	17430 lux	6038 lux
	18301 fc	1619 fc	561 fc
With FL-20G flood 45°	39160 lux	4576 lux	1780 lux
	3638 fc	425 fc	165 fc
Distance	3M	5M	7M
With PJ-BM-19	17460 lux	5532lux	2819 lux
	1622 fc	514 fc	262 fc
With PJ-BM-36	6063 lux	2055 lux	1024 lux
	563 fc	191 fc	95 fc