

<b>Model</b>	Forza 60B II
<b>Rated Power</b>	72W
<b>Input Voltage/Current</b>	DC15V/6A Max, AC100-240V 50/60Hz
<b>Beam Angle</b>	120°
<b>CCT</b>	2700K-6500K
<b>CRI</b>	Average 96
<b>TLCI</b>	Average 98
<b>TM-30 Rf</b>	Average 93
<b>TM-30 Rg</b>	Average 100
<b>Dimming</b>	0-100%
<b>Control</b>	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
<b>Effect</b>	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding
<b>Product Size</b>	Light fixture(without COB protective cap): 200 × 108 × 84mm / 7.87 × 4.25 × 3.31" Power Adapter(with holder base): 141 × 82 × 50mm / 5.55 × 3.23 × 1.97"
<b>Product Weight</b>	Light Fixture: 0.7kg / 1.54lb Power Adapter: 0.45kg / 0.99lb Power Cable 3M: 0.12kg / 0.26lb Reflector: 0.08kg / 0.18lb
<b>Master Carton Size</b>	200 × 108 × 84mm/7.87 × 4.25 × 3.31"
<b>Packing Quantity</b>	4
<b>Certification</b>	NCC, FCC-ID, KCC, RoHS

### Illumination (lux / fc)

#### Light Only

Distance	1M	2M	3M
<b>2700K</b>	2096 lux 195 fc	533 lux 50 fc	254 lux 24 fc
<b>3200K</b>	2235 lux 208 fc	569 lux 53 fc	270 lux 25 fc
<b>5600K</b>	2577 lux 239 fc	649 lux 60 fc	308 lux 29 fc
<b>6500K</b>	2529 lux 235 fc	646 lux 60 fc	307 lux 29 fc

**With Reflector**

<b>Distance</b>	<b>1M</b>	<b>2M</b>	<b>3M</b>
<b>2700K</b>	11430 lux 1062 fc	2540 lux 236 fc	1098 lux 102 fc
<b>3200K</b>	12170 lux 1131 fc	2731 lux 254 fc	1182 lux 110 fc
<b>5600K</b>	14350 lux 1333 fc	3186 lux 296 fc	1381 lux 128 fc
<b>6500K</b>	14090 lux 1309 fc	3183 lux 296 fc	1372 lux 127 fc

**With FL-11 Spot**

<b>Distance</b>	<b>1M</b>	<b>2M</b>	<b>3M</b>
<b>2700K</b>	28260 lux 2625 fc	6520 lux 606 fc	2823 lux 262 fc
<b>3200K</b>	30120 lux 2798 fc	6986 lux 649 fc	3045 lux 283 fc
<b>5600K</b>	34700 lux 3224 fc	8202 lux 762 fc	3563 lux 331 fc
<b>6500K</b>	34550 lux 3210 fc	8071 lux 750 fc	3540 lux 329 fc

**With FL-11 Flood**

<b>Distance</b>	<b>1M</b>	<b>2M</b>	<b>3M</b>
<b>2700K</b>	5472 lux 508 fc	1378 lux 128 fc	623 lux 58 fc
<b>3200K</b>	5887 lux 547 fc	1464 lux 136 fc	665 lux 62 fc
<b>5600K</b>	6852 lux 637 fc	1725 lux 160 fc	769 lux 71 fc
<b>6500K</b>	6810 lux 633 fc	1713 lux 159 fc	759 lux 71 fc

**With PJ-FMM-19**

<b>Distance</b>	<b>1M</b>	<b>2M</b>	<b>3M</b>
<b>2700K</b>	42640 lux 3961 fc	7650 lux 711 fc	3086 lux 287 fc
<b>3200K</b>	45560 lux 4233 fc	8154 lux 758 fc	3305 lux 307 fc
<b>5600K</b>	53070 lux 4930 fc	9377 lux 871 fc	3826 lux 355 fc
<b>6500K</b>	52950 lux 4919 fc	9352 lux 869 fc	3822 lux 355 fc

With PJ-FMM-36

Distance	1M	2M	3M
<b>2700K</b>	18050 lux 1677 fc	3320 lux 308 fc	1390 lux 129 fc
<b>3200K</b>	19210 lux 1785 fc	3583 lux 333 fc	1475 lux 137 fc
<b>5600K</b>	21980 lux 2042 fc	4113 lux 382 fc	1714 lux 159 fc
<b>6500K</b>	21650 lux 2011 fc	4109 lux 382 fc	1695 lux 157 fc