

Forza 60 II

Technical Data

Model	Forza 60 II
Rated Power	72W
Input Voltage/Current	DC15V/6A Max, AC100-240V 50/60Hz
Beam Angle	120°
CCT	5600K
CRI	95
TLCI	98
TM-30 Rf	Average 93
TM-30 Rg	Average 103
Dimming	0-100%
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Effect	INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Bad Bulb, Candle/Fire, Firework, Explosion and Welding
Product Size	Light Fixture(without COB protective cap): 200 × 108 × 84mm / 7.87 × 4.25 × 3.31" Power Adapter(with holder base): 141 × 82 × 50mm / 5.55 × 3.23 × 1.97"
Product Weight	Light Fixture: 0.84kg / 1.85lb Power Adapter: 0.45kg / 0.99lb Power Cable 3M: 0.12kg / 0.26lb Reflector: 0.08kg / 0.18lb
Master Carton Size	200 × 108 × 84mm/7.87 × 4.25 × 3.31"
Packing Quantity	4
Certification	NCC, FCC-ID, KCC, RoHS

Illumination (lux / fc)

Distance	1M	2M	3M
Light Only	3420 lux 318 fc	854 lux 79 fc	414 lux 38 fc
With Reflector	17620 lux 1637 fc	3980 lux 370 fc	1651 lux 153 fc
With FL-11 spot 10°	41580 lux 3863 fc	9666 lux 898 fc	4039 lux 375 fc
With FL-11 flood 45°	9478 lux 881 fc	2150 lux 200 fc	973 lux 90 fc
With PJ-FMM-19	60000 lux 5574 fc	10770 lux 1001 fc	4469 lux 415 fc
With PJ-FMM-36	23790 lux 2210 fc	4498 lux 418 fc	1850 lux 172 fc