

PTC-150 HD/SD PTZ Video Camera

Video format	1080p 59.94/50/29.97/25 1080i 59.94/50 720p 59.94/50 480i, 576i (on CVBS)
Image Sensor	1/2.8" type progressive scan CMOS sensor
Effective Pixels (approx.)	2.14 Mega pixels
S/N Ratio	50dB
Min. Illumination	Color : 0.4 lx B/W : 0.03 lx (F1.6, 1/30 sec, 50IRE, Gain: High)
Electronic Shutter	1/25~1/1250 sec (50/25Hz) 1/30~1/1500 sec (59.94/29.97Hz)
Zoom Ratio	30x Optical Zoom
Gamma Control	Off / Normal / Standard Mode 1-4
Iris Control	Auto / Manual
Digital Noise Reductions	Yes
On-Screen Display (OSD)	English
White Balance	AWB, MWB, One push WB, Outdoor, Indoor, Fluorescent
AGC / Gain Control	Auto / Manual Max. Gain Limit
Mirror / Flip Image	Yes
Focus Mode	Auto / Manual
Panning / Tilting Range	Pan: 270° , Tilt: +90° to -20°
Panning / Tilting Speed	Manual: 1~150°/Sec Swing: 1~150°/Sec
Preset	50 Position
Focal Length	f=4.3 mm (WIDE) to 129 mm (TELE) F1.6 to F4.7
Field of View (Horizontal, Wide)	Approx. 63.7° (WIDE END) / 2.3° (TELE END)
Image Compensation	Day & Night Function
Video Output	3G-SDI x1 HDMI x1 CVBS x1
Tally LED	Dual color (Red, Green)
Filter	M52.0 x 0.75 Thread with UV Protection
Protocol	VISCA, DVIP
Remote Control Interface and Transmit Distance	RS-422: Transmit up to 1000m DVIP (RJ45): 100m
F/W Update	USB
IR Control	Yes
Camera Control Unit	RMC-180/RMC-300C
Tripod Mount	1/4-20 UNC
Options	WM-1/WM-10
Color	Black/White
Dimension (LxWxH)	173 x 189 x 219 mm
Weight	2.7 kg
Operating Temp. Range	0~40 °C
Power	DC 12V 29W

What's in the Box

Content

1 x PTC-150 Unit
1 x IR remote controller
1 x PTC-150 Thank You Card
1 x Ceiling mount bracket-A
1 x Ceiling mount bracket -B
6 x Ceiling mount bracket screw M3*4mm
1 x DC 12V Power Adaptor
1 x Power Cord
1 x A tightrope