

Model	PavoSlim 60B	PavoSlim 120B
Rated Power	72W	150W
Input Voltage/Current	DC(Battery)14.4-26V DC(Battery)7.4V × 2 AC100-240V 50/60Hz	DC24V DC(Battery)14.4-26V AC100-240V 50/60Hz
CCT	2700K-6500K	
CRI	Average 95	
TLCI	Average 97	
TM-30 Rf	Average 95	
TM-30 Rg	Average 102	
SSI (3200K)	83	
SSI (5600K)	73	
Dimming	0-100%	
Control	On-board, Remote Controller, NANLINK APP, DMX/RDM	
Special Effects	CCT Loop, INT Loop, Flash, Pulse, Storm, TV, Paparazzi, Candle/Fire, Bad Bulb, Firework, Explosion and Welding	
Product Size	Light Fixture: 306.3 × 300.65 × 18.6mm / 12.06 × 11.84 × 0.73" Control Unit: 146.45 × 111.48 × 175mm / 5.77 × 4.39 × 6.89"	Light Fixture: 602 × 306.3 × 18.6mm / 23.7 × 12.06 × 0.73" Control Unit: 140.3 × 111.48 × 203mm / 5.52 × 4.39 × 7.99"
Product Weight	Light Fixture: 0.91kg / 2.01lb Control Unit: 1.37kg / 3.02lb	Light Fixture: 1.65kg / 3.64lb Control Unit: 1.84kg / 4.06lb
Certifications	RoHS, CE, UKCA, FCC-ID, NCC, KCC	

# *Illumination ( lux / fc )*

## *PavoSlim 60B*

### Light Only

Distance	0.5M	1M	3M
2700K	25160 lux / 2337 fc	7063 lux / 656 fc	840 lux / 78 fc
3200K	26350 lux / 2448 fc	7433 lux / 691 fc	871 lux / 81 fc
4300K	27700 lux / 2573 fc	7766 lux / 721 fc	902 lux / 84 fc
5600K	29180 lux / 2711 fc	8156 lux / 758 fc	955 lux / 89 fc
6500K	28140 lux / 2614 fc	7893 lux / 733 fc	918 lux / 85 fc

### With Softbox and Lite Diffuser

Distance	0.5M	1M	3M
2700K	12060 lux / 1120 fc	2987 lux / 277 fc	342 lux / 32 fc
3200K	12790 lux / 1188 fc	3130 lux / 291 fc	352 lux / 33 fc
4300K	13430 lux / 1248 fc	3284 lux / 305 fc	371 lux / 34 fc
5600K	14150 lux / 1315 fc	3470 lux / 322 fc	391 lux / 36 fc
6500K	13750 lux / 1277 fc	3356 lux / 312 fc	377 lux / 35 fc

### With Softbox and Standard Diffuser

Distance	0.5M	1M	3M
2700K	5040 lux / 468 fc	1148 lux / 107 fc	131 lux / 12 fc
3200K	5282 lux / 491 fc	1199 lux / 111 fc	137 lux / 13 fc
4300K	5560 lux / 517 fc	1258 lux / 117 fc	143 lux / 13 fc
5600K	5868 lux / 545 fc	1328 lux / 123 fc	152 lux / 14 fc
6500K	5694 lux / 529 fc	1282 lux / 119 fc	146 lux / 14 fc

*PavoSlim 120B*

**Light Only**

<b>Distance</b>	<b>0.5M</b>	<b>1M</b>	<b>3M</b>
2700K	46250 lux / 4297 fc	15480 lux / 1438 fc	1945 lux / 181 fc
3200K	48830 lux / 4536 fc	16210 lux / 1506 fc	2035 lux / 189 fc
4300K	53540 lux / 4974 fc	17940 lux / 1667 fc	2244 lux / 208 fc
5600K	52200 lux / 4979 fc	17620 lux / 1637 fc	2210 lux / 205 fc
6500K	53600 lux / 4979 fc	18010 lux / 1673 fc	2253 lux / 209 fc

**With Softbox and Lite Diffuser**

<b>Distance</b>	<b>0.5M</b>	<b>1M</b>	<b>3M</b>
2700K	22420 lux / 2083 fc	6495 lux / 603 fc	784 lux / 73 fc
3200K	23400 lux / 2174 fc	6812 lux / 633 fc	819 lux / 76 fc
4300K	26130 lux / 2427 fc	7593 lux / 705 fc	910 lux / 85 fc
5600K	25660 lux / 2384 fc	7435 lux / 691 fc	888 lux / 82 fc
6500K	26240 lux / 2438 fc	7601 lux / 706 fc	912 lux / 85 fc

**With Softbox and Standard Diffuser**

<b>Distance</b>	<b>0.5M</b>	<b>1M</b>	<b>3M</b>
2700K	10360 lux / 962 fc	2542 lux / 236 fc	301 lux / 28 fc
3200K	10850 lux / 1008 fc	2676 lux / 249 fc	311 lux / 29 fc
4300K	12040 lux / 1119 fc	2952 lux / 274 fc	344 lux / 32 fc
5600K	11810 lux / 1097 fc	2913 lux / 271 fc	337 lux / 31 fc
6500K	12100 lux / 1124 fc	2968 lux / 276 fc	345 lux / 32 fc