

Model	PavoTube II 30C
Rated Power	60W
Input Voltage/Current	DC15V/4A Max, AC100-240V 50/60Hz PD3.0(12-20V)30W Min
CCT	2700K-7500K(G/M±150)
CRI	Average 97
TLCI	Average 98
TM-30 Rf	Average 94
TM-30 Rg	Average 101
Dimming	0-100%
Control	On-board, 2.4G, Bluetooth, NANLINK APP, DMX/RDM
Effect	Hue Loop, CCT Loop, INT Loop, CCT Flash, HUE Flash, CCT Pulse, Hue Pulse, Storm Auto, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding
Product Size	φ48×1170mm/φ1.89×46.06"
Product Weight	Light Fixture: 1.4kg / 3.09lb Power Adapter: 0.2kg / 0.44lb Power Cable 3M: 0.05kg / 0.11lb
Master Carton Size	455 × 305 × 1300mm / 17.91 × 12.01 × 51.18" (1KIT) 305 × 305 × 1300mm / 12.01 × 12.01 × 51.18" (2KIT) 375 × 190 × 1300mm / 14.76 × 7.48 × 51.18" (4KIT)
Quantity of Boxes Per Carton	1KIT: 8 / 2KIT: 6 / 4KIT: 2
Certification	CE, UKCA, RoHS, PSE, KCC, FCC-ID, NCC, KC

Illumination (lux / fc)

Distance	0.5M	1M	2M	3M
2700K	1720 lux	581 lux	174 lux	88 lux
	160 fc	54 fc	16 fc	8 fc
3200K	1767 lux	599 lux	179 lux	90 lux
	164 fc	56 fc	17 fc	8 fc
5600K	1910 lux	647 lux	193 lux	97 lux
	177 fc	60 fc	18 fc	9 fc
6500K	1944 lux	660 lux	196 lux	99lux
	181 fc	61 fc	18 fc	9 fc
7500K	1925 lux	654 lux	195 lux	98 lux
	179 fc	61 fc	18 fc	9 fc
R	870 lux	303 lux	88 lux	43 lux
	81 fc	28 fc	8 fc	4 fc
G	1819 lux	642 lux	181 lux	91 lux
	169 fc	60 fc	17 fc	8 fc
B	300 lux	106 lux	30 lux	16 lux
	28 fc	10 fc	3 fc	1 fc