

Model	<i>PavoTube T8-7X</i>
Rated Power	8W
Input Voltage/Current	DC5V/2A
CRI	Average 96
TLCI	Average 97
CCT	2700K-7500K(G/M)
Dimming	On-board Control: 0, 20, 40, 60, 80, 100 NANLINK APP Control: 0-100
Control	On-board, Bluetooth, DMX/RDM, Wire Control
Effect	Hue Loop, CCT Loop, INT Loop, Flash, Pulse, Storm, Police Car, TV, Paparazzi, Candle/Fire, Disco, Bad Bulb, Firework, Explosion and Welding.
Pixel Effect	Hue Loop, CCT Loop, INT Loop, Multicolor, Fade, Process, Scroll, Fire, Rainbow, Driving
Product Size	φ39×1002mm / φ1.53×39.44"
Product Weight	0.28kg / 0.61lb
Certifications	CE, UKCA, NCC

Illumination (lux / fc)

PavoTube T8-7X

Distance	0.3M	0.5M	1M
2700K	700 lux / 65 fc	328 lux / 30 fc	106 lux / 10 fc
3200K	711 lux / 66 fc	334 lux / 31 fc	107 lux / 10 fc
4300K	719 lux / 67 fc	340 lux / 32 fc	110 lux / 10 fc
5600K	757 lux / 70 fc	362 lux / 34 fc	117 lux / 11 fc
6500K	783 lux / 73 fc	371 lux / 34 fc	121 lux / 11 fc
7500K	791 lux / 73 fc	379 lux / 35 fc	124 lux / 12 fc
R	256 lux / 24 fc	121 lux / 11 fc	40 lux / 4 fc
G	619 lux / 58 fc	297 lux / 28 fc	94 lux / 9 fc
B	116 lux / 11 fc	55 lux / 5 fc	18 lux / 2 fc