## **Owl Bar Specifications**

#### OVERVIEW

# **OWL LABS**°

General	Usage	Certifications & Compatibility
Built-in components: 4 beamforming microphones, digital pan-tilt-zoom camera, 1 speaker, The Nest device management platform. Table stand/wall mounting included.	Owl Intelligence System™: Powered by the OIS™ using AI computer vision and movement and voice cues to automatically focus on active speakers	Device Pairing: Wirelessly pairs with one Meeting Owl (3 or Pro), or one Meeting Owl and one Whiteboard Owl, in the same meeting space
Enclosure: All-in-one enclosure with integrated table stand/wall mount	Wireless Pairing: Wireless pairing with the Meeting Owl and the Whiteboard Owl supported Speaker Framing: Automatic digital PTZ to correctly frame in-room participants based on where they're seated Camera Switching: Intelligent camera switching between the Owl Bar and the Meeting Owl to show the best view of the room for remote participants	VC Platforms: All web-based video conferencing platforms, including Zoom, Microsoft Teams, Google Meet, Slack, and others VC Certifications: Microsoft Teams and Zoom certifications coming by end of 2023 USB Mode: Plug and Play to work with host or in-room computer
Device Management: The Nest		
Displays Supported: 2		
Display Resolution: Up to 4K		
Processor: Qualcomm 8250		

### **TECHNICAL SPECIFICATIONS**

Camera	Speakers & Microphones	Interfaces & Power
Resolution: 4K Camera: 30 MP Horizontal FOV: 114° Vertical FOV: 73°	Pickup Range: 18ft / 5.5m Beamforming Elements: 4 omnidirectional microphones Add-on Mics: Option to connect one Expansion Mic when paired with Meeting Owl 3 Speakers: 1 high-fidelity speaker Audio Processing & Noise Suppression: OIS Output: 82 dBSPL at 1m	HDMI Out (#): 2* HDMI In (#): 1* USB Type: USB 3.0: 1x Type C, 1x Type A Network: 10/100/1000 Ethernet; 2.4GHz and 5.0 GHz WiFi * Reserved for future use

### MANAGEMENT

Setup & What's in the Box	Environmental	Security & Warranty
What's in the box: • Owl Bar • USB cable • Table / Wall Mount • Mounting hardware • Power supply • DC Cable • AC Cable • User documentation Mounting Options:	Operating Temperature: 32° to 95° F (0° to 35° C) Storage Temperature: -4° to 140° F (-20° to 60° C) Humidity: 10% to 90% Operating Voltage/Power: 19V	Secure Boot Processes enabled Communication Ports: Locked down; only allowed to communicate with secure protocols <u>Owl Labs security details</u> Standard: 2-year limited hardware warranty included Owl Care: 3-year limited hardware warranty, white glove onboarding support, and one no-questions-asked device replacement
<ul> <li>Included mounting bardware englise tableton estup or wall mounting</li> </ul>		

Included mounting hardware enables tabletop setup or wall mounting