

# amaran

## amaran COB 60d S Data Sheet

### Main Features

- **Ultra-High Color Quality** 65W Output Daylight Bowens Mount Point-Source LED
- **Upgraded High SSI LEDs:** SSI (D56): **86+** — Significantly Improved Spectral Continuity & Light Quality
- **Increased CRI, TLCI, TM-30 and SSI Scores** for Super Accurate Color Rendering
- CRI: **96+**, TLCI: **99+**, TM-30 Rf: **96**, TM-30 Rg: **100**
- **37,800 lux @ 1m** with Hyper Reflector (Mini)
- **Full Size Universal Bowens Accessory Mount**
- Included **Diffusion Cover** for Reflector
- Daylight CCT: **5,600K**
- **Stepless Dimming** from **0 to 100%**
- **Sidus Link** App Compatible
- **Passive V-Mount Quick Release Lock**
- Included **Dual Sony NP-F Battery Plate**
- **D-Tap Battery Compatible**<sup>1</sup>
- **Compact & Lightweight:** Just Over 11x11x11cm and 695g
- **1/4-20in Mounting Point**
- **Tilting Stand Mount with Umbrella Holder**
- **8 Lighting FX:** Paparazzi, Fireworks, Lightning, Faulty Bulb, TV, Pulse, Strobe, & Explosion
- Integrated **Silent Cooling** System
- Click Control Knob to **Toggle Through Intensity Presets**

<sup>1</sup> D-Tap Power Cable (DC 5.5mm) Sold Separately

### Target Audience

With its ultra-high color quality, compact and lightweight body design, and convenient operation, the amaran COB 60d S is perfect for creators, videographers, and indie filmmakers who need to pack light without sacrificing exceptional spectral and image quality.

For creators lighting home studios or livestream setups, the significantly improved spectral quality of the COB 60d S will ensure accurate skin tone reproduction with industry-leading color quality.

Its super compact and lightweight form factor coupled with versatile power solutions with NP-F or D-Tap batteries make the COB 60d S ideal for creating on-the-go. And with its full-size Bowens Mount and intuitive Sidus Link app control, the compact versatility of the COB 60d S makes it an essential addition to any content creator, videographer, or indie filmmaker's lighting arsenal.

### amaran COB 60d S Photometrics

CCT	Source	0.5m	1m	3m
5,600K	No Reflector	11,550 lux / 1,068 fc	2,940 lux / 273 fc	344 lux / 32 fc
	Hyper Reflector (Mini)	134,700 lux / 12,514 fc	37,800 lux / 3,512 fc	4,200 lux / 390 fc



### Product Description

The amaran COB 60d S is an ultra-compact 65W daylight Bowens Mount point-source light with integrated controls, full Bowens Mount versatility, and an upgraded LED chipset for enhanced color quality and spectral reproduction.

Featuring an all-new dual-blue LED chipset design, the COB 60d S has improved spectral continuity to achieve stunning spectral reproduction of an ultra-high SSI (D56) of 96, a 19% increase in SSI from its predecessor. The enhanced color accuracy of the COB 60d S can also be seen in its increased CRI [96], TLCI [99], TM-30 RF [96], and TM-30 RG [100] values.

Equipped with a full-size universal Bowens Mount, the miniature COB 60d S is compatible with the largest selection of modifiers on the market, including the Light Box 45x45, Light Dome SE, Light Dome Mini II, and Aputure Lantern, making it an incredibly versatile multi-tool. For additional versatility, the COB 60d S can also be used with an umbrella with the included Tilting Stand Mount.

With its small stature as compact as a camera, the COB 60d S contains a powerhouse LED that can output 37,800+ lux at 1 meter when paired with the matching Hyper Reflector (Mini). Its miniature form factor houses an intuitive LCD screen and control knob interface that seamlessly blends into the body of the fixture, with the ability to adjust the light in 1% increments and toggle through intensity presets with ease.

Using its integrated Sidus Mesh technology, the COB 60d S can be controlled wirelessly via the Sidus Link app, granting it access to an extended range of intuitive controls as well as 8 lighting effects, including Paparazzi, Fireworks, Lightning, Faulty Bulb, TV, Pulse, Strobe, and Explosion.

In addition to the included AC Power Supply, the fixture can be powered using the included Dual Sony NP-F Battery Plate or a D-Tap Battery<sup>1</sup>, which can easily be attached to the V-Mount Quick Release, located on the side of the unit for easy operation. The COB 60d S is the perfect light for creating on the move and can also be used with its matching Handheld Bracket<sup>2</sup> via the 1/4-20in Mounting Point for the ultimate mobile lighting kit.

<sup>1</sup> D-Tap Power Cable (DC 5.5mm) Sold Separately

<sup>2</sup> Handheld Bracket for amaran COB 60d/x Sold Separately



## What's in the Box

Name	Qty
amaran COB 60d S	1
Bowens Mount Protection Cover	1
Bowens Mount Hyper Reflector (Mini)	1
Diffusion Cover for Hyper Reflector (Mini)	1
1/4-20in Mounting Pin	1
Tilting Stand Adapter with Umbrella Mount	1
Dual NP-F Battery Plate for DC Barrel (5.5mm)	1
AC Power Supply	1
AC Power Cable	1
EPP Carrying Case	1

## Sales & Shipping Information

<b>Product Name</b>		amaran COB 60d S
<b>SKU</b>	<b>EU Plug</b>	APA0020A11
	<b>UK Plug</b>	APA0020A13
<b>EAN</b>	<b>EU Plug</b>	6971842185955
	<b>UK Plug</b>	6971842185979
<b>Packing Dimensions</b>		32.7 x 27.0 x 14.8cm 12.87 x 10.63 x 5.83in
<b>Net Weight</b>		2.133kg / 4.70lbs
<b>Gross Weight</b>		2.621kg / 5.78lbs
<b>Carton Quantity</b>		2 pcs
<b>Carton Dimensions</b>		34.5 x 31.5 x 29cm 13.58 x 12.4 x 14.42in
<b>Carton Weight</b>		5.89kg / 12.99lbs

## amaran COB 60d S Specifications

<b>CCT</b>		5,600K
<b>CRI</b>		96+
<b>TLCI</b>		99+
<b>CQS</b>		95+
<b>SSI (D56)</b>		86+
<b>TM-30 RF (Average)</b>		96
<b>TM-30 RG (Average)</b>		100
<b>Max Power Consumption</b>		77W
<b>Max Power Output</b>		65W
<b>Lumens</b>		7,195lm
<b>Beam Angle</b>	<b>No Reflector</b>	107.8°
	<b>Hyper Reflector (Mini)</b>	13.9°
<b>Operating Voltage</b>	<b>DC Power Supply</b>	19V / 4.73A
	<b>AC Power Supply</b>	100V ~ 240V / 1.5A
	<b>V-Mount Battery</b>	12V ~ 16.8V
<b>Operating Temperature</b>		-10°C ~ 40°C / 14°F ~ 104°F
<b>Storage Temperature</b>		-20°C ~ 80°C / -4°F ~ 176°F
<b>Control Methods</b>		On-board, Sidus Link App
<b>Firmware Upgradeable</b>		Sidus Link
<b>Wireless Operating Range (Bluetooth)</b>		≤80m / ≤262.5ft
<b>Screen Type</b>		LCD
<b>Cooling Method</b>		Active Cooling
<b>Dimensions</b>	<b>Lamp Head w/o Mounting Bracket</b>	11.7 x 11.1 x 11.1cm 4.61 x 4.37 x 4.37in
	<b>Lamp Head w/ Mounting Bracket</b>	11.7 x 11.1 x 23.1cm 4.61 x 4.37 x 9.09in
	<b>Power Supply</b>	147 x 64 x 37.4mm 5.79 x 2.52 x 1.47in
	<b>Power Cable</b>	410cm / 161.4in
	<b>Battery Plate</b>	11 x 8.6 x 2.2cm 4.33 x 3.39 x 0.87in
<b>Weight</b>	<b>Lamp Head</b>	695g / 1.53lbs
	<b>Power Supply</b>	500g / 1.1lbs
	<b>Battery Plate</b>	111g / 0.24lbs
	<b>Total with Case</b>	2.621kg / 5.78lbs